

Catalog Number	
Project Notes	

Recessed Architectural 2x2

Features & Functionality

- Purpose** 2'x2' new construction and LED troffer for indoor IP20 projects
- Material** Steel body with polycarbonate diffuser lens
- Finish** Painted White
- Mounting** Standard, suspended, T-Bar, retrofit, or recessed mount
- Color Temp.** 3000°K, 3500°K, 3700°K, 4000°K and 5000°K.
- Output** 2'x2' model: up to 4,680 Lumens
- Dimming** 0-10V, compatible with most dimming systems
- Voltage** 100-277 VAC
- Lifespan** 50,000 hours
- Warranty** 5-year warranty



Lumen Information

SIZE	LUMENS	WATTAGE	EFFICACY
2'x2'	3,120	24	130Lm/W
2'x2'	3,900	30	130Lm/W
2'x2'	4,680	36	130Lm/W



Product Selection Guide

Example: AT-AR-22-30-40-A



PRODUCT	SERIES	WATTAGE	COLOR TEMP
AT-AR – Attain LED Troffer	22 – 2'x2' Square	24 – 24W	30 – 3000°K
		30 – 30W	35 – 3500°K
		36 – 36W	37 – 3700°K
			40 – 4000°K
			50 – 5000°K

Dimensional Information

