

Catalog Number	
Project Notes	

Recessed Architectural 2x4

Features & Functionality

Purpose	2'x4' new construction and LED troffer for indoor IP20 projects
Material	Steel body with polycarbonate diffuser lens
Finish	Painted White
Mounting	Standard, suspended, T-Bar, retrofit, or recessed mount
Color Temp.	3000°K, 3500°K, 3700°K, 4000°K and 5000°K.
Output	2'x4' model: up to 7,800 Lumens
Dimming	0-10V, compatible with most dimming systems
Voltage	100-277 VAC
Lifespan	50,000 hours
Warranty	5-year warranty



Lumen Information

SIZE	LUMENS	WATTAGE	EFFICACY
2'x4'	4,680	36	130Lm/W
2'x4'	5,200	40	130Lm/W
2'x4'	5,850	45	130Lm/W
2'x4'	6,500	50	130Lm/W
2'x4'	7,800	60	130Lm/W



Product Selection Guide

Example: AT-AR-22-30-40-A

PRODUCT	SERIES	WATTAGE	COLOR TEMP
AT-AR – Attain LED Troffer	24 – 2'x4' Rectangular	36 – 36W	30 – 3000°K
		40 – 40W	35 – 3500°K
		45 – 45W	37 – 3700°K
		50 – 50W	40 – 4000°K
		60 – 60W	50 – 5000°K

Dimensional Information

