

Catalog Number	
Project Notes	

Track Head- Round

Features & Functionality

Purpose	Adjustable LED track head for indoor IP20 projects.
Concept	COB LED track head featuring Cameta™ lens.
Material	Aluminum body.
Finish	Available in White, Silver and Black finishes.
Mounting	Compatible with H-type, J-type, L-type and Global type track mounts
LED	CREE COB LED
Color Temp.	2700°K, 3000°K, 4000°K and 5000°K available. Up to 95 CRI
Optics	Cameta™ lens with anti-glare
Beam Spread	15°, 24°, 38° and 60° beam spreads available
Output	8.5W: up to 700 Lumens 15W: up to 1,358 Lumens 25W: up to 2,154 Lumens 36W: up to 3,052 Lumens 45W: up to 4,245 Lumens
Dimming	100% to 10%. Compatible with most dimmers
Voltage	120V
Lifespan	50,000 hours
Warranty	5-year warranty



Lumen Information

LUMENS	WATTAGE	EFFICACY
700Lm	8.5W	82Lm/W
1,358Lm	15W	91Lm/W
2,154Lm	25W	86Lm/W
3,052Lm	36W	85Lm/W
4,245Lm	45W	94Lm/W




Product Selection Guide

Example: AT-TR-RD-15-30-95-24-A-SV-G


PRODUCT	SERIES	WATTAGE	COLOR TEMP	CRI	OPTICS	BODY COLOR	MOUNTING
AT-TR – Attain LED Track Head	RD – Round	08 – 8.5W ¹	27 – 2700°K	82 – 82 CRI ¹	15 – 15°	WH – White	H – H-type
		15 – 15W	30 – 3000°K	95 – 95 CRI ³	24 – 24°	SV – Silver	J – J-type
		25 – 25W	40 – 4000°K		38 – 38°	BK – Black	L – L-type
		36 – 36W ²	50 – 5000°K		60 – 60°		G – Global type
		45 – 45W					

¹ 24°, 38° or 60° beam spread only. ³ 95 CRI Available for 2700°K or 3000°K.
² 24° or 38° beam spread only. ⁴ 25W Model only.


Mounting




H-type



J-type



L-type



Global

Dimensional Information

